

NKB1000/KBD1000/KB1000

Network Keyboard & Control Keyboard & Dome keyboard



Features:

Keyboard to Control

- Dahua High Speed Dome (all models)
- Dahua Standalone DVR (KBD1000 & NKB1000 only)
- Dahua Network High Speed Dome (NKB1000 only)
- Network Video Server (NKB1000 only)

Connection

- NKB1000: RS485, RS422, USB, RS232 & Network
- KBD1000: RS485, RS422, USB & RS232
- KB1000 : RS485, RS422 & USB

(RS422 reserved for all models)

Functions

- Three Dimensional Joystick Control of PTZ Functions
- Preset Position, Auto Scan, Auto Pan, Auto Tour & Pattern

Auxiliary Functions

- On-Screen Menu & User Operation Procedure Tips
- Connect to SmartPSS via USB (NKB1000 only)

3-axis

USB
Control

RJ-45
port



Technical Specification

Model

Model	NKB1000	KBD1000	KB1000
-------	---------	---------	--------

General

Keyboard Key panel	Electromechanical		
Joystick	3-axis, vector-solving, with twisting, return to-center head		
Keyboard Connector	RJ-45, RS232, RS485, RS422, USB	RS232, RS485, RS422, USB	RS485, RS422, USB
Keyboard Communication	Direct Mode, Network Mode	Direct Mode	Direct Mode
Direct Mode	Interface: 1 RS232/2 RS485 DVR Protocol: DH-2 Dome Protocol: DH-SD1/PELCO-D/ PELCO-P, etc	Interface: 1 RS232/2 RS485 Dome Protocol: DH-SD1/PELCO-D/ PELCO-P, etc	Interface: 2 RS485 Dome Protocol: DH-SD1/PELCO-D/ PELCO-P, etc
Network Mode	Interface: RJ45 DVR/Network Dome: IP Address/Port/ Protocol	N/A	N/A
Display	LCD, 75.2mm×33.85mm		
Maximum Number of Users	64 (including "admin")		

Max RS485 Addresses (Each User)	256
Max Number of PTZ (IPC) That Can be Added over Network (Each User)	2048

Environmental

Power Supply	Power adapter, input 100V~240V 50Hz/60Hz, output DC12V/1000mA
Power Consumption	5W
Working Temperature	-10℃~+55℃
Working Humidity	10% ~ 90%
Atmosphere Pressure	86kpa~106kpa
Dimension	330mm×160(140)mm×37.5(21)mm (W×D×H)(height: 100mm including joystick)
Weight	2.5kg (Including package)